

SINCE  
1998

solaire  
A Lagnuovo Initiative



## SOLAIRE X3 MAX



## FEATURES

### Intelligence For Easy Maintenance And Economy

- Built-in export power control
- Remote setting and upgrading
- 24 hours operation monitoring
- Smart I-V Curve Diagnosis supported
- Night-time reactive power compensation
- Aluminium AC cable connection available
- Power line communication (PLC)(Optional)
- Fuse free design with smart string current monitoring
- Smart air cooling technique results in long lifetime of fans
- Advanced heat dissipation technology makes the system more than 5% lighter and smaller

### Safety & Reliability

- IP66 protection level
- AFCI protection (Optional)
- AC terminal temperature detection
- Both AC&DC SPDs(Type II) inside, Type I+II SPD is optional

### More Energy Harvest

- Maximum efficiency up to 99%
- 180-1000Vdc MPPT voltage range
- Maximum 12 MPPTs, 2 strings per MPPT tracker
- 150% PV oversizing input, 110% overloading output
- Maximum 32A MPPT current

	75K	80K	100K	110K	120K	125K	136K	150K
<b>DC INPUT</b>								
Max. PV array input power [kWp]	120	120	150	165	180	188	204	225
Max. PV input voltage [V]				1100				
Nominal input voltage [V]*	580/600	580/600	580/600	580/600	580/600	580/600	730/785	730/785
Startup voltage [V]				200				
MPP tracker voltage range [V]				180-1000				
No. of MPP trackers	9	9	9	9	12	12	12	12
Strings per MPP tracker				2				
Max. PV input current per MPPT [A]				32				
Isc PV Array Short Circuit current per MPPT [A]				46				
<b>AC OUTPUT</b>								
Rated AC output power [kW]	75	80	100	110	120	125	136	150
Rated AC output current [A]*	113.7/108.7	121.3/116	1516/145	1667/1595	1819/174	1894/181.2	1571/145.4	1732/160.4
Max. AC output apparent power [kVA]	75	88	110	121	132	132	149.6	165
Max. AC output current [A]*	113.7/108.7	1334/1276	1667/1595	1834/1754	200/191.3	200/191.3	1728/160	1906/1765
Nominal AC voltage [V]			220/380, 230/400 , 3/N/PE, 3/PE				500/540,3P3W+PE	
AC voltage range [V]**			304 ~ 480				425 ~ 594	
Nominal AC frequency/AC frequency range [Hz]**				50/60; ±5				
THDi (Rated power) [%]				<3				
Power Factor range				0.8 leading ~ 0.8 lagging				
<b>SYSTEM DATA</b>								
MPPT efficiency [%]				99.9				
Max. efficiency [%]	98.6	98.6	98.6	98.6	98.6	98.6	99.0	99.0
Ingress protection				IP66				
Operating ambient temperature range [° C]				-30~+60 (Derating above 45)				
Max. operation altitude [m]				4000 (Derating above 3000)				
Relative humidity [%]				0~100				
Dimensions [W×H×D] [mm]				985×660×327.5				
Weight [kg]	83	83	83	83	87	87	87	87
Cooling concept				Smart fan cooling				
Communication interfaces				RS485 / USB / DRM / PLC(Optional)				
Optional monitoring dongle				Pocket WiFi/LAN/4G				
Display				LCD(16x2, optional)/LEDx4				
<b>PROTECTION</b>								
Over/under voltage protection				YES				
DC isolation protection				YES				
Grid monitoring				YES				
DC injection monitoring				YES				
Residual current detection				YES				
Anti-islanding protection				YES				
String fault detection				YES				
SPD (DC/AC)				Type II / Type II				
Arc-fault circuit interrupter(AFCI)				Optional				
AC terminals over temperature detection				YES				
AC auxiliary power supply(APS)				Optional				
Power line communication(PLC)				Optional				
<b>STANDARD</b>								
Safety				IEC/EN 62109-1; IEC/EN 62109-2; NB/T 32004				
EMC				IEC/EN 61000; NB/T 32004				
Certification			EN 50549; AS4777.2; VDE4105; IEC 61727; IEC 62116; IEC 61683; IEC 60068; EN 50530; NB/T 32004					

\* The two data refer to different grid voltage 220V/230V or 500V/540V

\*\* The AC voltage and the frequency range may vary from different country codes

V2.8 Information may be subject to modify without notice. 650.00001.00